




Fisa Tehnica



Dale Royal

Material		ISO 2070	Ecologic, reciclabil ,stabilizat UV, polipropilenă.
Dimensiuni		EN 427	301,6 x 301,6 mm. 1 m ² /cutie=11 dale. 5 m ² / bax = 55 dale.
Grosime		EN 428	13,20 mm.
Greutate		EN 430	1 dala: 0,245 kg. 5 m ² : 14,10 kg (bax).
Greutate maxima tolerata		QUALIFIED TEST	400 tone / 1 m ² = 4000 kg/dm ²
Rezistenta la lumina		EN 14836 (>3) ISO 105-B02 (1-8)	4-5 7-8
Rezistenta la vreme / UV Floorida Test (1-5)		ASTM D1435 ASTM G154 Cycle A	4/5
Rezistenta la alunecare		DIN51 130 SSEN-13893	R10 / V10 >0,4
Rezistenta la impact		ISO179/1eA ASTM D746	+23 °C = 20 kJ/m ² / -20 °C = 5 kJ/m ² C15 kJ/m ²
Categoria de incendiu		EN ISO 11925-2	Efl
Certificare CE		EN 14041	0402-CPD-P605080A

Impachetare	Cantitate m ² /cutie/bax	Cantitate pe palet	Dimensiune palet
Cutie	1 m ² = 7 dale	1 palet = 84 cartons = 84 m ²	1,26 x 0,96 x 1,16 m = 1,40 m ³ , 270 kg greutate
Bax	5 m ² = 55 dale	1 palet = 36 cartons = 180 m ²	1,30 x 0,98 x 2,40 m = 3,06 m ³ , 533 kg greutate